

Web Based Single Door Controller...

FINGERPRINT CONTROLLER

BF-630

FEATURES

- Can Standalone or to be a Fingerprint/RFID Reader of BF-660/670 in multi-door Control.
- Anti Pass Back.
- Door Bell Support .
- Double Badge Control.
- Low Power Consumption.
- Optical-based Technology.
- On-line Viewing Door Status Via Web Browser.
- Optional: Audible Indicators or Export Transactions to USB Disk.
- Build in Http Server, Can Use Web Browser to Make System Management.
- Selectable Time Zone for Fp+Pin/Card+Pin/Lock Release/Exit Button.
- Support 50 Holidays, Internet Time Server, 40 Sets Function Key Setting, 32 Departments, 32 Designations, 64 Time Sets, 64 Time Zones, 32 Groups.



SPECIFICATION

False Rejection Rate (FRR): Less Than 0.01%.

False Acceptance Rate (FAR): Less Than 0.001%.

Verification Time: FP: Less Than 2.0 sec./RFID: Less Than 1.0 sec.

Registration Time: FP: Less Than 3.0 sec./RFID: Less Than 2.0 sec.

RFID Function: 125 KHz(EM/TM), 13.56 MHz(Mifare)<Optional>.

Capacity: 950 Persons (1,900 Templates), 2 Templates for 1 User.

Verification Method: Fingerprint, Fingerprint+Password, Fingerprint+RFID, Fingerprint+Password+RFID.

Communication Speed: 10/100M, Auto Crossing.

Communication: RS-485→Relay Box (BF-20).

Log Data: 32,768 Transactions.

2000 System Log.

WG Output Support, Fire Alarm Input.

Keypad: 10 Number Key+6 Function Key+1 Door Bell .

Display: 128 X 64 Dots LCD, 3 LED.

Operating Temperature: 0°C ~ 65°C

Storage Temperature: -20°C ~ 85°C

Operating Humidity: 5% ~ 95%

Storage Humidity: 5% ~ 95%

Power: DC 9 ~ 30 V, 1 A.

Dimensions: 145 X 125 X 33 mm

Weight: 350 g.

WEB BASED SOFTWARE



Access Control & Time and Attendance

HOW TO ORDER

BF-630 SERIES

BF-630-E: EM

BF-630-M: Mifare

BF-630-X: EM+Mifare

BF-630-E-V: EM+Voice

BF-630-M-V: Mifare+Voice

BF-630-X-V: EM+Mifare+Voice

OPTION ACCESSORIES

RELAY BOX: BF-20

RFID CARD/Keyfob:

EM/Temic/Mifare+Temic Card, EM/TM

Keyfob

Power Adaptor



TYPICAL APPLICATION

